product details

44870 VWFL 50W 12V GU5,3 FS1

Product description:	44870 VWFL 50W 12V GU5,3 FS1
Product code:	4050300272832
Quantity:	Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300272832

Applications	
Dimmable	Yes
Burning position	any

Categorizations	
ILCOS	HRGS//UB-50-12-GU5,3-51/60

General Description	
Base (standard designation)	GU5.3
Filament setting	Axial
Mercury-free	Yes

Technical - Electrical Data	
Nominal wattage	50 W
Rated wattage	50 W
Nominal voltage (product)	12 V

Technical - Geometries	
Overall length	46.00 mm
Contact spacing	5.3 mm
Diameter	51.0 mm
Length	46 mm

Technical - Lifespan	
Nominal lamp life time	3000 h
Rated lamp life time	3000 h

Technical - Light Technical Data	
Luminous intensity	800 cd
Beam angle	60 °
Color temperature	3000 K
Color rendering index Ra	100
Rated starting time	0 s

Packaging units

Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300272832	Folding carton box contains 1 Piece	46,000 mm x 46,000 mm x 58,000 mm	38,000 g (0,000 g)	0,123 Cubic dec.
4050300533841	Shipping carton box contains 20 Piece	123,000 mm x 122,000 mm x 214,000 mm	836,000 g (0,000 g)	3,074 Cubic dec.

Subject to change without notice. Errors and omission excepted.
© 2010 OSRAM GmbH

product details

44870 VWFL 50W 12V GU5,3 FS1

Every professional knows that light is not always the same when it comes to illuminating heatsensitive objects. In this case the DECOSTAR 51 dichroic reflector lamp is the right choice because most of the heat produced by the lamp is emitted through the rear of the reflector. This reduces the heat in the light beam by up to 66 %. It is therefore easier to present heat-sensitive objects in the right light.

- Brilliant accent light
- Dichroic reflector reduces the heat in the light beam by up to 66 %
- Approved for use in open luminaires to IEC 60598-1
- Average life: 2,000 h
- Dimmable
- R_a=100
- Color temperature: 20 W - 2,800 K; 35 W - 2,900 K; 50 W - 2,950 K
- Base: GU5.3
- UV filter

For light distribution curves go to www.osram.com

Subject to change without notice. Errors and omission excepted.
© 2010 OSRAM GmbH